

XHTML 1.0 Quick Reference

```
<?xml version="1.0" encoding="UTF-8" ?>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"  
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"  
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Frameset//EN"  
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd">
```

```
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en">  
</html>
```

```
<head>  
<title>PAGE TITLE HERE</title>  
<meta name="Description" content="PAGE DESCRIPTION" />  
<meta name="Keywords" content="PAGE SUBJECT KEYWORDS" />  
<base href= "DEFAULT URL PATH" target= "DEFAULT FRAME" />  
<style type="text/css">  
CSS STYLE INFORMATION  
</style>  
</head>
```

```
<body onload="JAVASCRIPT" onunload="JAVASCRIPT">  
XHTML CODE  
</body>
```

```
<!-- Comments go here. -->
```

```
<big>Big text</big> renders in a larger font.  
<small>Small text</small> renders in a smaller font.  
<sub>Subscript text</sub> renders subscript.  
<sup>Superscript text</sup> renders superscript.
```

```
<strong>Strongly emphasized text</strong> renders bold.  
<em>Emphasized text</em> renders italic.  
<ins>Inserted text</ins> renders underlined.  
<del>Deleted text</del> renders strikethrough.
```

```
<blockquote>A block quote</blockquote> renders indented on both sides.  
<q>A quotation</q> renders normally.  
<cite>A citation</cite> renders italic.
```

```
<h1-6>Headings</h1-6> render differently and larger to smaller from 1 to 6.  
<p>Paragraphs</p> render in separate text blocks.
```

XHTML 1.0 Quick Reference

`<abbr title="MEANING">`An abbreviation`</abbr>` renders normally.
`<acronym title="MEANING">`An acronym`</acronym>` renders normally.
`<address>`An address`</address>` renders italic.
`<dfn>`A definition`</dfn>` renders italic.

`<code>`Computer code`</code>` renders monospaced.
`<kbd>`Keyboard text`</kbd>` renders monospaced.
`<pre>`Preformatted text`</pre>` renders monospaced.
`<samp>`Sample program output`</samp>` renders monospaced.
`<tt>`Teletype text`</tt>` renders monospaced.
`<var>`A variable`</var>` renders italic.

`<div>`A page division`</div>` renders as a block element.
``A span of content`` renders as an inline element.

`<dl>`
`<dt>`Definition term renders left-justified.`</dt>`
`<dd>`Definition data renders with a left indent.`</dd>`
`</dl>`

``
``Ordered list items render as a numbered list.``
``

``
``Unordered list items render bulleted.``
``

``An anchor link`` renders underlined blue.
``

`<hr />` A horizontal rule renders as a line across the page.
`
` A line break ends a line of content.

`<iframe src="URI" name="TARGET NAME" scrolling="yes|no|auto">`
Alternate content for non-supporting browsers goes inside the element that creates an inline frame.
`</iframe>`

`<object id="ID" type="application/x-shockwave-flash" data="FILENAME.swf">`
`<param name="movie" value="FILENAME.swf" />`
Alternative content for non-supporting browsers goes inside the object element.
`</object>`

XHTML 1.0 Quick Reference

```
<object id="MediaPlayer1" classid="CLSID:22d6f312-b0f6-11d0-94ab-0080c74c7e95"
codebase="http://activex.microsoft.com/activex/controls/mplayer/en/nsmp2inf.cab#
Version=5,1,52,701" standby="Loading Microsoft Windows Media Player
components..." type="application/x-oleobject">
<param name="fileName" value="AUDIO FILE OR PLAYLIST" />
<param name="animationatStart" value="true" />
<param name="transparentatStart" value="true" />
<param name="autoStart" value="true" />
<param name="showControls" value="true" />
<param name="Volume" value="-300" />
<embed type="application/x-mplayer2"
pluginspage="http://www.microsoft.com/Windows/MediaPlayer/" src="AUDIO FILE
OR PLAYLIST" name="MediaPlayer1" autostart="1" showcontrols="1" volume="-300"
/>
</object>
```

```
<script type="text/javascript">
//
Javascript goes here.
//]]&gt;
&lt;/script&gt;
&lt;noscript&gt;
Alternative content for non-supporting browsers goes here.
&lt;/noscript&gt;</pre></div><div data-bbox="142 525 827 682" data-label="Text"><pre>&lt;img src="URI" usemap="#MAPNAME" /&gt;
&lt;map name="MAPNAME"&gt;
&lt;area shape="rect" coords="TOPLEFTX, TOPLEFTY, BOTTOMRIGHTX,
BOTTOMRIGHTY" alt="ALTERNATIVE TEXT" /&gt;
&lt;area shape="circle" coords="center-x, center-y, right-edge-x, right-edge-y"
alt="alternative text" /&gt;
&lt;area shape="poly" coords="first-point-x, first-point-y, second-point-x, second-point-
y..." alt="alternative text" /&gt;
&lt;/map&gt;</pre></div><div data-bbox="142 699 808 750" data-label="Text"><pre>&lt;form name="form name" enctype="encoding type" accept="filetype"
method="get|post" onreset="javascript" onsubmit="javascript" action="script uri"&gt;
&lt;/form&gt;</pre></div><div data-bbox="142 769 539 819" data-label="Text"><pre>&lt;fieldset&gt;
&lt;legend&gt;Identifying Title for a Fieldset&lt;/legend&gt;
&lt;/fieldset&gt;</pre></div><div data-bbox="142 838 750 872" data-label="Text"><pre>&lt;label for="field id"&gt;Label for Field&lt;/label&gt;&lt;label for="field id"&gt;Label for
Field&lt;/label&gt;</pre></div><div data-bbox="489 934 507 952" data-label="Page-Footer"><p>3</p></div>
```

XHTML 1.0 Quick Reference

```
<input type="text|checkbox|radio|password|file|hidden|submit|reset|button|image"
size="box character width" maxlength="max character entry" id="field id" name="field
name" src="button graphic" value="field value / default text / button title" disabled=
"disabled" readonly= "readonly" checked="checked" />
```

```
<select name= "field name" id= "field id">
<optgroup label= "option group title">
<option>Option</option>
</optgroup>
</select>
```

```
<textarea id="field id" name="field name" wrap="soft|hard|off" rows="character rows"
cols="character width">
Text to appear in the text area goes here.
</textarea>
```

```
<frameset rows|columns= "pixels|percent%|*|proportion*, ...">
<frame src="uri" name="target name" scrolling="auto|yes|no" noresize="noresize" />
<noframes>
<body>Alternative content for browsers that don't support frames goes here.</body>
</noframes>
</frameset>
```

```
<table><tr><td>
</td></tr></table>
```

```
<th>This can be used in place of TD to indicate a table heading.</th>
```

```
<caption>Table Caption</caption>
```

```
<colgroup span= "number of columns">
<col id="id" | class="class" | style="css" />
```

```
...
</colgroup>
```

```
<thead>
Table rows and cells in the table header go here.
</thead>
```

```
<tfoot>
Table rows and cells in the table footer go here.
</tfoot>
```

```
<tbody>
Table rows and cells in the table body go here.
</tbody>
```